



# ISOVOLT titan|neo

Robust, reliable stationary X-ray generators

The ISOVOLT titan|neo generator powers a range of radiographic inspection technology—delivering the most reliable, consistent results in even the highest accuracy applications. So you can increase precision and inspect multiple parts each day.

**Increased reproducibility:** Reduce exposure times for various materials in several operation modes with high, stable radiation and fluctuations <0.05%.

**Greater dependability:** An extended tube range and maximum current ensure enhanced imaging contrast and high penetration power.

**Unmatched flexibility:** Its modular design includes intelligent tube integration and permanent system monitoring—offering unmatched ramp-up times\* and a 100% duty cycle for continuous operation in inline systems\*\*.

## Features



POWERFUL PERFORMANCE



PERMANENT SYSTEM MONITORING



MODULAR DESIGN FOR EASY INTEGRATION



CONVENIENT, USER-FRIENDLY CONTROLS



BUILT-IN SAFETY FEATURES



\*Depending on permissible tube data.

\*\*Subject to operational generator cooling.

# Technical specifications<sup>†</sup>

High voltage generator	160 kV Unipolar	225 kV Unipolar
Max out voltage kV	-160	-225
Max out current mA	45	45
Max out power kW	4,5 (limited by tube spec)	4,5 (limited by tube spec)
Insulation	Oil	Oil
Housing dim wxdxh	340 x 945 x 750 mm 13.38" x 37.20" x 29.52"	340 x 945 x 750 mm 13.38" x 37.20" x 29.52"
Weight	200 kg , 440.92 lbs	200 kg , 440.92 lbs
Tube voltage		
Presele and settings	From 5 to 160kV in 1kV	From 5 to 225kV in 1kV
Dig display of set and act values	3 digits (set); 4 digits (act)	3 digits (set) ; 4 digits (act)
Display resolution	1kV (set); 0,1 kV (act)	1kV (set) ; 0,1 kV (act)
Accuracy	<1%	<1%
Reproducibility	<0,01%	<0,01%
Temperature drift	<80ppm/K	<80ppm/K
Tube current		
Presele and settings	From 0,1 to 45mA in 0,1mA	From 0,1 to 45mA in 0,1mA
Dig display of set and act values	3 digits	3 digits
Display resolution	0,1 mA	0,1 mA
Accuracy	<1%	<1%
Reproducibility	<0,25%	<0,25%
Temperature drift	<100ppm/K	<100ppm/K
Exposure time		
Programmable timer	1	1
Presele and setting	1 .. 9999 s	1 .. 9999 s
Dig display of set and act values	4 digits	4 digits
Prewarning	Audible and visible	Audible and visible
Presele and setting	2 .. 120 s or deactivated	2 .. 120 s or deactivated
Programmed mode		
Number of storable programs	250	250
Warm-up	Auto mode based on real time clock	Auto mode based on real time clock
X-ray tube set up	8 Tube selectable from a database of 40 pre-programmed tubes	8 Tube selectable from a database of 40 pre-programmed tubes
Operation history	Stored on SD	Stored on SD
Warm-up history	Stored on SD	Stored on SD
Control module		
Dimension wxdxh	440 x 114 x 295 mm 17.32" x 4.48" x 11.61"	440 x 114 x 295 mm 17.32" x 4.48" x 11.61"
Weight	3.8 kg, 8.37 lbs	3.8 kg, 8.37 lbs
Connected loads		
Power connection	1N PE 230 V ± 10% 50/60 Hz 3N PE 400/230 V ±10%, 50/60 Hz, 3-Phase, Grounded Neutral TN-S or TN-C-S Mains (Star Connected System, Optional 3-Phase Isolation Transformer)	1N PE 230 V ± 10% 50/60 Hz 3N PE 400/230 V ±10%, 50/60 Hz, 3-Phase, Grounded Neutral TN-S or TN-C-S Mains (Star Connected System, Optional 3-Phase Isolation Transformer)
Grounding	Separate Grounding for X-ray Tube and High Voltage Generator (Minimum 6 mm2)	Separate Grounding for X-ray Tube and High Voltage Generator (Minimum 6 mm2)
Mains fuses	63 A (1N PE) or 20 A (3N PE) Time-Delay Fuses, Customer-Supplied	63 A (1N PE) or 20 A (3N PE) Time-Delay Fuses, Customer-Supplied
Operating temperature range	0°C to +40°C	0°C to +40°C
Storage temperature range	-30°C to +70°C	-30°C to +70°C

<sup>†</sup>Technical specifications are preliminary and subject to change.

High voltage generator	320 KV Bipolar	450 KV Bipolar	240 HR
Max out voltage kV	320	450	-240
Max out current mA	45	45	3
Max out power kW	4.5 (limited by tube spec)	4.5 (limited by tube spec)	0.320 (limited by tube spec)
Insulation	Oil	Oil	Oil
Housing dim wxdxh	(340 x 945 x 750) + (340 x 945 x 540) mm (13.38" x 37.20" x 29.52") + (13.38" x 37.20" x 21.25")	(340 x 945 x 750) + (340 x 945 x 540) mm (13.38" x 37.20" x 29.52") + (13.38" x 37.20" x 21.25")	340 x 945 x 750 mm (13.38" x 37.20" x 29.52")
Weight	200+140 (kg) 440.92 + 308.64 (lbs)	200+140 (kg) 440.92 + 308.64 (lbs)	170 kg, 374.78 lbs
Tube voltage			
Preselect and settings	From 10 to 320 kV in 1 kV	From 10 to 450 kV in 1 kV	From 5 to 240kV in 1kV
Dig display of set and act values	3 digits (set); 4 digits (act)	3 digits (set) ; 4 digits (act)	3 digits
Display resolution	1kV (set); 0,1 kV (act)	1kV (set) ; 0,1 kV (act)	1kV
Accuracy	<1%	<1%	<1%
Reproducibility	<0,01%	<0,01%	<0,01%
Temperature drift	<80ppm/K	<80ppm/K	<80ppm/K
Tube current			
Preselect and settings	From 0,1 to 45mA in 0,1mA	From 0,1 to 45mA in 0,1mA	From 0,01 to 3mA in 0,001mA
Dig display of set and act values	3 digits	3 digits	4 digits
Display resolution	0,1 mA	0,1 mA	0,001 mA
Accuracy	<1%	<1%	<1%
Reproducibility	<0,25%	<0,25%	<0,25%
Temperature drift	<100ppm/K	<100ppm/K	<100ppm/K
Exposure time			
Programmable timer	1	1	1
Preselect and setting	1 .. 9999 s	1 .. 9999 s	1 .. 32767 s (xs-control)
Dig display of set and act values	4 digits	4 digits	5 digits
Prewarning	Audible and visible	Audible and visible	Audible and visible
Preselect and setting	2 .. 120 s or deactivated	2 .. 120 s or deactivated	2 .. 255 s or deactivated
Programmed mode			
Number of storable programs	250	250	—
Warm-up	Auto mode based on real time clock	Auto mode based on real time clock	Automated Intelligent Tube conditioning
X-ray tube set up	8 Tube selectable from a database of 45 pre-programmed tube	8 Tube selectable from a database of 45 pre-programmed tubes	—
Operation history	Stored on SD	Stored on SD	—
Warm-up history	Stored on SD	Stored on SD	—
Control module			
Dimension wxdxh	440 x 114 x 295 mm 17.32" x 4.48" x 11.61"	440 x 114 x 295 mm 17.32" x 4.48" x 11.61"	—
Weight	3.8 kg, 8.37 lbs	3.8 kg, 8.37 lbs	—
Connected loads			
Power connection	1N PE 230 V ± 10% 50/60 Hz 3N PE 400/230 V ±10%, 50/60 Hz, 3-Phase, Grounded Neutral TN-S or TN-C-S Mains (Star Connected System, Optional 3-Phase Isolation Transformer)	1N PE 230 V ± 10% 50/60 Hz 3N PE 400/230 V ±10%, 50/60 Hz, 3-Phase, Grounded Neutral TN-S or TN-C-S Mains (Star Connected System, Optional 3-Phase Isolation Transformer)	1N PE 230 V ± 10% 50/60 Hz Aux, 1N PE 230 V ± 10% 50/60 Hz Main
Grounding	Separate Grounding for X-ray Tube and High Voltage Generator (Min. 6 mm2)	Separate Grounding for X-ray Tube and High Voltage Generator (Min. 6 mm2)	Separate Grounding for X-ray Tube and High Voltage Generator (Min. 6 mm2)
Mains fuses	63 A (1N PE) or 20 A (3N PE) Time-Delay Fuses, Customer-Supplied	63 A (1N PE) or 20 A (3N PE) Time-Delay Fuses, Customer-Supplied	13,5 A (1N PE) integrated into Aux switch 13,5 A (1N PE) integrated into Main switch
Operating temperature range	0°C to +40°C	0°C to +40°C	0°C to +40°C
Storage temperature range	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C



GE Sensing & Inspection Technologies GmbH  
Bogenstr. 41  
22926 Ahrensburg  
Germany

Tel.: +49 4102 807 0  
Fax: +49 4102 807 277  
E-mail: [xray.info@ge.com](mailto:xray.info@ge.com)

GE Inspection Technologies  
201 Beltway Green Blvd.  
Pasadena, Texas 77503

Tel.: +1 281 542 3600

[industrial.ai/inspection-technologies](http://industrial.ai/inspection-technologies)

© 2018 General Electric Company. All rights reserved. Specifications subject to change without notice. GE is a registered trademark of General Electric Company. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.